


Type	Profile (mm)	Performance for Typical Lengths (Thermal Resistance - °C/w)									
		Plain or Alocromed Finish (1,3)					Matt Black Anodised Finish (2)				
		50mm	75mm	100mm	125mm	150mm	50mm	75mm	100mm	125mm	150mm
41DN		1.7	1.4	1.2	1.1	1.0	1.5	1.2	1.0	0.93	0.90
43DN		2.8	2.1	1.7	1.6	1.4	2.4	1.8	1.5	1.3	1.2
44DN		2.3	1.8	1.5	1.4	1.25	1.8	1.4	1.2	1.1	1.0
46DN		1.9	1.6	1.3	1.0	0.9	1.3	1.1	0.9	0.7	0.6
	*NB 3.30 DIA. EXTRUDED HOLES SUIT No.6 SELF TAPPING SCREW OR M4 THREAD (NO DRILLING REQUIRED)										
47DN		3.2	2.7	2.2	1.8	1.6	2.5	2.1	1.7	1.3	1.2
48DN		2.1	1.8	1.5	1.1	1.0	1.45	1.2	0.95	0.75	0.7
49DN		1.8	1.5	1.0	0.90	0.80	1.4	1.3	0.85	0.75	0.70

50DN			1.6	1.3	0.95	0.85	0.75	1.2	1.1	0.80	0.72	0.65
------	-----------------------------------------------------------------------------------	--	-----	-----	------	------	------	-----	-----	------	------	------